

DISC TILLER RUBBER TYPE

MANDA RUBBER



agromaster®

We know the soil

www.agromaster.com

MANDA 16

MANDA 20

MANDA 24

MANDA 28

MANDA 32

MANDA, Disc Tiller Rubber Type

Agromaster; provides modern equipment, Disc Tiller (Disc Rotary Harrow Combination) to Farmers for the soil cultivation. It operates by not causing a base in the field due to the fact that each disk is independent in the various working conditions. Agromaster Disc Tiller cultivates the soil in depth, prevents erosion and puts the base occurring away. The equipment operates by not causing base according to the soil narrow and allows rain water and oxygen to work in the adjustments of group of Rotary Harrow Combination (Wringer) in our product are performed through a hydraulic piston. Because of the fact that is taken onto the equipment through hydraulic piston of wringer group in Transport Mode, the load on the back of the tractor is in the lowest level. Furthermore, products, having less work wideness, can be manufactured for especially wood gaps upon the demands.



Technical Specifications*	Unit	MANDA 16	MANDA 20	MANDA 24	MANDA 28	MANDA 32
Number of Disc	pcs	16	20	24	28	32
Disc Space	mm	250				
	ft.in.	10"				
Working Width	mm	2000	2500	3000	3500	4000
	ft.in.	79"	98"	118"	138"	157"
Disc Diameter	mm	560-610				
	ft.in.	22" - 24"				
Weight (560 mm)	kg	1300	1730	1815	2050	2340
	lbs	2866	3814	4001	4519	5159
Weight (610 mm)	kg	1350	1800	1900	2150	2450
	lbs	2976	3968	4189	4740	5401
Required Power	hp	65-75	80-100	100-115	110-130	130-150

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.



agromaster®

+90 332 235 64 23

info@agromaster.com

www.agromaster.com

Buyukkayacak OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TÜRKİYE

