

SPRING TINE TILLERS

T4 / T4R Foldable



agromaster®
We know the soil

www.agromaster.com

T4 **35**
 T4 **40**
 T4 **45**
 T4 **50**
 T4 **55**
 T4 **60**

T4, Spring Tine Tiller 4 Row Foldable


Technical Specifications*	Unit	T4 35	T4 40	T4 45	T4 50	T4 55	T4 60
Number of Disc	pcs	35	40	45	50	55	60
Total Width (W)	mm	3600	4100	4600	5100	5600	6100
	ft.in.	11'10"	13'5"	15'1"	16'9"	18'5"	20'
Total Length (L)	mm	1500	1500	1500	1500	1500	1500
	ft.in.	4'11"	4'11"	4'11"	4'11"	4'11"	4'11"
Total Height (H)	mm	T	1350	1350	1350	1350	1350
	ft.in.	4'5"	4'5"	4'5"	4'5"	4'5"	4'5"
Height (H1)	mm	430	430	430	430	430	430
	ft.in.	1'5"	1'5"	1'5"	1'5"	1'5"	1'5"
Working Depth (Max.)	mm	200	200	200	200	200	200
	ft.in.	8"	8"	8"	8"	8"	8"
Working Width	mm	3600	4100	4600	5100	5600	6100
	ft.in.	11'10"	13'5"	15'1"	16'9"	18'5"	20'
Tine Dimensions	mm	30x10	30x10	30x10	30x10	30x10	30x10
	ft.in.	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'
Space Between Tine	mm	125	125	125	125	125	125
	ft.in.	5"	5"	5"	5"	5"	5"
Frame Size	mm	80x80	80x80	80x80	80x80	80x80	80x80
	ft.in.	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"
Required Power	hp	90-100	100-110	115-125	130-140	145-160	160-175
Weight	kg	580	650	720	790	860	930
	lbs	1278	1433	1587	1741	1895	2050

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.

T4R **35**T4R **40**T4R **45**T4R **50**T4R **55**T4R **60****T4R, Spring Tine Tiller 4 Row Foldable With Roller**

Technical Specifications*	Unit	T4R 35	T4R 40	T4R 45	T4R 50	T4R 55	T4R 60
Number of Disc	pcs	35	40	45	50	55	60
Total Width (W)	mm	3600	4100	4600	5100	5600	6100
	ft.in.	11'10"	13'5"	15'1"	16'9"	18'5"	20'
Total Length (L)	mm	1500	1500	1500	1500	1500	1500
	ft.in.	4'11"	4'11"	4'11"	4'11"	4'11"	4'11"
Length (L1)	mm	2365	2365	2365	2365	2365	2365
	ft.in.	7'9"	7'9"	7'9"	7'9"	7'9"	7'9"
Total Height (H)	mm	1350	1350	1350	1350	1350	1350
	ft.in.	4'5"	4'5"	4'5"	4'5"	4'5"	4'5"
Height (H1)	mm	430	430	430	430	430	430
	ft.in.	1'5"	1'5"	1'5"	1'5"	1'5"	1'5"
Working Depth (Max.)	mm	200	200	200	200	200	200
	ft.in.	8"	8"	8"	8"	8"	8"
Working Width	mm	3600	4100	4600	5100	5600	6100
	ft.in.	11'10"	13'5"	15'1"	16'9"	18'5"	20'
Tine Dimensions	mm	30x10	30x10	30x10	30x10	30x10	30x10
	ft.in.	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'
Space Between Tine	mm	125	125	125	125	125	125
	ft.in.	5"	5"	5"	5"	5"	5"
Frame Size	mm	80x80	80x80	80x80	80x80	80x80	80x80
	ft.in.	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"
Roller Diameter (D)	mm	315	315	315	315	315	315
	ft.in.	12"	12"	12"	12"	12"	12"
Required Power	hp	90-100	100-110	115-125	130-140	145-160	160-175
Weight	kg	980	1060	1140	1220	1300	1380
	lbs	2160	2336	2513	2689	2866	3042

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.



agromaster®

+90 332 235 64 23

info@agromaster.com

www.agromaster.com

Buyukkayacik OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TÜRKİYE

