

LAND LEVELLER WITH WHEEL

TKT / TKTH



agromaster®
We know the soil

www.agromaster.com

TKT-TKTH **200**

TKT-TKTH **250**

TKT-TKTH **300**

TKT-TKTH **350**

TKT-TKTH **400**

TKT, TKTH, Land Leveller With Wheel

Agromaster Levelling Blades are mounted to tractors by three point linkage system. These Levelling Blades can be used in various purposes like making a field way, land levelling, opening ditches and filling. Blades are produced from special steel to prevent corrosion and breakings. Also both sides of these removable blades can be used. By the help of depth wheels the control of levelling depth can be done more easily.



Technical Specifications*	Unit	TKT 200 TKTH 200	TKT 250 TKTH 250	TKT 300 TKTH 300	TKT 350 TKTH 350	TKT 400 TKTH 400
Overall Width (W)	mm	2000	2500	3000	3500	4000
	ft.in.	6'7"	8'2"	9'10"	11'6"	13'1"
Scraper Height (H)	mm	700	700	700	700	700
	ft.in	2'4"	2'4"	2'4"	2'4"	2'4"
Working Width	mm	2000	2500	3000	3500	4000
	ft.in.	6'7"	8'2"	9'10"	11'6"	13'1"
Linkage of Suspension System	CAT	II	II	II	II	II
Number of Blades	pcs	1	1	1	1	1
Blade Rotation		Hydraulic / Mechanic				
Offset Adjustment		Hydraulic / Mechanic				
Take-angle Adjustment		Hydraulic / Mechanic				
Required Power	hp	50-60	60-70	70-80	85-90	95-110
Total Weight	kg	720	760	800	860	920
	lbs	1587	1675	1763	1895	2028
1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch				* Manufacturer reserves rights to change them without notice.		



Blade Rotation



Offset adjustment



Take-angle adjustment



agromaster®

+90 332 235 64 23

info@agromaster.com

www.agromaster.com

Buyukkayacik OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TÜRKİYE

