

DISC PLOUGH SQUARE
HOLLOW FRAME TYPE

PDP



agromaster®
We know the soil

www.agromaster.com

PDP **663**
PDP **664**
PDP **665**
PDP **666**

PDP, Disc Plough Square Hollow Frame Type

This machine is mounted to tractor's hydraulic lifting unit and universal three point linkage system. Profile frame disc plough is manufactured with 120x120 mm profile frame as 2, 3, 4, 5 and 6 discs. 660x6 mm or 710x6 mm diameter discs are made with 50-52 RH hardness corrosion-proof steel and resistance to cracking. The discs can be adjusted according to the soil conditions by means of position and direction angle.



Technical Specifications*	Unit	PDP 663	PDP 664	PDP 665	PDP 666
Number of Disc	pcs	3	4	5	6
Total Width (W)	mm	1085	1325	1563	1800
	ft.in	3'6"	4'4"	5'1"	5'10"
Total Length (L)	mm	1710	2200	2690	3180
	ft.in	5'7"	7'2"	8'9"	10'5"
Total Height (H)	mm	1520	1520	1520	1520
	ft.in	4'11"	4'11"	4'11"	4'11"
Working Depth	mm	250	250	250	250
	ft.in	0'10"	0'10"	0'10"	0'10"
Working Width	mm	990	1320	1650	1980
	ft.in	3'3"	4'4"	5'4"	6'6"
Space Between Bodies	mm	545	545	545	545
	ft.in	1'10"	1'10"	1'10"	1'10"
Chassis Size	mm	120x120			
	ft.in	0'4" x 0'4"			
Required Power	hp	55-60	70-80	85-90	100-110
Dia of disc	mm	660	660	660	660
		2'2"	2'2"	2'2"	2'2"
Dia of disc (optional)	mm	710 (Op.)	710 (Op.)	710 (Op.)	710 (Op.)
		2'4"	2'4"	2'4"	2'4"
Category		II	II	II	II-III
Weight	kg	435	560	660	910
	lbs	959	1234	1455	2006

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inc

* Manufacturer reserves rights to change them without notice.



Middle Lever



Furrow Wheel



Curve Adjustment Lever



agromaster®

+90 332 235 64 23

info@agromaster.com

www.agromaster.com

Buyukkayacik OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TÜRKİYE

