

SPRING TINE TILLERS

T4 / T4R



agromaster®
We know the soil

www.agromaster.com

T4 19
T4 21
T4 23
T4 25
T4 27
T4 29
T4 31

T4, Spring Tine Tiller 4 Row


Technical Specifications*	Unit	T4 19	T4 21	T4 23	T4 25	T4 27	T4 29	T4 31
Number of Disc	pcs	19	21	23	25	27	29	31
Total Width (W)	mm	2250	2500	2750	3000	3250	3500	3750
	ft.in.	7'5"	8'2"	9'	9'10"	10'8"	11'6"	12'4"
Total Length (L)	mm	1500	1500	1500	1500	1500	1500	1500
	ft.in.	4'11"	4'11"	4'11"	4'11"	4'11"	4'11"	4'11"
Total Height (H)	mm	1350	1350	1350	1350	1350	1350	1350
	ft.in.	4'5"	4'5"	4'5"	4'5"	4'5"	4'5"	4'5"
Height (H1)	mm	430	430	430	430	430	430	430
	ft.in.	1'5"	1'5"	1'5"	1'5"	1'5"	1'5"	1'5"
Working Depth (Max.)	mm	200	200	200	200	200	200	200
	ft.in.	8"	8"	8"	8"	8"	8"	8"
Working Width	mm	2250	2500	2750	3000	3250	3500	3750
	ft.in.	7'5"	8'2"	9'	9'10"	10'8"	11'6"	12'4"
Tine Dimensions	mm	30x10	30x10	30x10	30x10	30x10	30x10	30x10
	ft.in.	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'
Space Between Tine	mm	125	125	125	125	125	125	125
	ft.in.	5"	5"	5"	5"	5"	5"	5"
Frame Size	mm	65x65	65x65	65x65	65x65	65x65	65x65	65x65
	ft.in.	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"
Required Power	hp	50-55	55-60	65-70	70-75	75-80	80-90	95-100
Weight	kg	340	390	440	490	540	590	640
	lbs	749	859	970	1080	1190	1300	1410

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.

T4R **19**
T4R **21**
T4R **23**
T4R **25**
T4R **27**
T4R **29**
T4R **31**

T4R, Spring Tine Tiller 4 Row With Roller

Technical Specifications*	Unit	T4R 19	T4R 21	T4R 23	T4R 25	T4R 27	T4R 29	T4R 31
Number of Disc	pcs	19	21	23	25	27	29	31
Total Width (W)	mm	2250	2500	2750	3000	3250	3500	3750
	ft.in.	7'5"	8'2"	9'	9'10"	10'8"	11'6"	12'4"
Total Length (L)	mm	1500	1500	1500	1500	1500	1500	1500
	ft.in.	4'11"	4'11"	4'11"	4'11"	4'11"	4'11"	4'11"
Length (L1)	mm	2365	2365	2365	2365	2365	2365	2365
	ft.in.	7'9"	7'9"	7'9"	7'9"	7'9"	7'9"	7'9"
Total Height (H)	mm	1350	1350	1350	1350	1350	1350	1350
	ft.in.	4'5"	4'5"	4'5"	4'5"	4'5"	4'5"	4'5"
Height (H1)	mm	430	430	430	430	430	430	430
	ft.in.	1'5"	1'5"	1'5"	1'5"	1'5"	1'5"	1'5"
Working Depth (Max.)	mm	200	200	200	200	200	200	200
	ft.in.	8"	8"	8"	8"	8"	8"	8"
Working Width	mm	2250	2500	2750	3000	3250	3500	3750
	ft.in.	7'5"	8'2"	9'	9'10"	10'8"	11'6"	12'4"
Tine Dimensions	mm	30x10	30x10	30x10	30x10	30x10	30x10	30x10
	ft.in.	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'	1"x1/32'
Space Between Tine	mm	125	125	125	125	125	125	125
	ft.in.	5"	5"	5"	5"	5"	5"	5"
Frame Size	mm	65x65	65x65	65x65	65x65	65x65	65x65	65x65
	ft.in.	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"	3"x3"
Roller Diameter	mm	315	315	315	315	315	315	315
	ft.in.	12"	12"	12"	12"	12"	12"	12"
Required Power	hp	50-55	55-60	65-70	70-75	75-80	80-90	95-100
Weight	kg	550	610	670	730	790	850	910
	lbs	1212	1344	1477	1609	1741	1873	2006

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.



agromaster®

+90 332 235 64 23

info@agromaster.com

www.agromaster.com

Buyukkayacik OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TÜRKİYE

