

MOULDBOARD RIDGER FIXED AND FOLDABLE

MR



agromaster®
We know the soil

www.agromaster.com

MR 2
MR 3
MR 4
MR 5

MR, Mouldboard Ridger Fixed and Foldable

The primary soil tillage machine is mounted and trailed from tractor's hydraulic lifting unit and universal three point linkage system. Therefore transportation to the field can be easily done. Furrow opener is placed over adjustable angle chassis. It has an opportunity to enter between rows as demanded width due to its adjustable moldboards. The usage aim of the machine is to open furrows between rows and ridging for row-planted seeds such as; corn, sunflower, cotton, etc

Fixed



Foldable



Technical Specifications*	Unit	MR 2	MR 3	MR 4	MR 5
Number of The Bodies	pcs	2	3	4	5
Total Width (W)	mm	1300	2100	2900	3700
	ft.in.	4'3"	6'11"	9'6"	12'2"
Total Length (L)	mm	700	800	800	800
	ft.in	2'4"	2'7"	2'7"	2'7"
Total Height (H)	mm	1250	1250	1250	1250
	ft.in	4'1"	4'1"	4'1"	4'1"
Distance Between Bodies (B)	mm	600-950	600-950	600-950	600-950
	ft.in	1'12"-3'1"	1'12"-3'1"	1'12"-3'1"	1'12"-3'1"
Furrow Bottom Depth	mm	250	250	250	250
	ft.in.	10"	10"	10"	10"
Furrow Width	mm	300-340-360	300-340-360	300-340-360	300-340-360
	ft.in.	12"-13"-14	12"-13"-14	12"-13"-14	12"-13"-14
Working Dept (max)	mm	200-350	200-350	200-350	200-350
	ft.in.	8"-14	8"-14	8"-14	8"-14
Required Power	hp	35-40	40-45	60-70	80-90
Weight	kg	147	223	370	450
	lbs	324	491	815	992

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.





agromaster®

+90 332 235 64 23

✉ info@agromaster.com

🌐 www.agromaster.com

🏠 Buyukkayacik OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TÜRKİYE

