

SUBSOILER

DK



agromaster®

We know the soil

www.agromaster.com



DK **1**
DK **2**
DK **3**
DK **4**
DK **5**
DK **7**

DK, Subsoiler

The primary soil tillage machine is mounted from tractor's hydraulic lifting unit and universal three point linkage system. Therefore transportation to the field can be easily done. The single-beam concept of the CLI allows an under beam clearance of 1.175m at working depths from 15 to 40cm. Available in 3 and 4m working width to combine with a seed drill combination or even with a Qualidisc drill.



Technical Specifications*	Unit	DK 1	DK 2	DK 3	DK 4	DK 5	DK 7
Number of Tines	pcs	1	2	3	4	5	7
Total Length (L)	mm	700	850	1300	1300	1900	1900
	ft.in.	2'4"	2'9"	4'3"	4'3"	6'3"	6'3"
Total Width (W)	mm	1100	1800	1800	2550	2550	3300
	ft.in.	3'7"	5'11"	5'11"	8'4"	8'4"	10'10"
Total Height (H)	mm	1620	1620	1620	1620	1620	1620
	ft.in.	5'4"	5'4"	5'4"	5'4"	5'4"	5'4"
Clearance	mm	650-900	650-900	650-900	650-900	650-900	650-900
	ft.in.	2'2"-2'12"	2'2"-2'12"	2'2"-2'12"	2'2"-2'12"	2'2"-2'12"	2'2"-2'12"
Distance Between Tines (W2)	mm	-	800-1600	400-600-800	400	200	400
	ft.in.	-	2'7"-5'3"	1'4"-1'12"-5'3"	1'4"	8"	1'4"
Working Depth	mm	550-750	550-750	550-750	550-750	550-750	550-750
	ft.in.	1'10"-2'6"	1'10"-2'6"	1'10"-2'6"	1'10"-2'6"	1'10"-2'6"	1'10"-2'6"
Required Power	hp	70-80	90-100	110-120	150-160	180-200	200-250
Total Weight	kg	200	240	565	700	920	1170
	lbs	440	529	1203	1543	2028	2579

1 inch = 25,4 mm - 1 inch = 0,083 feet (foot) - 1 feet (foot) = 12 inch

* Manufacturer reserves rights to change them without notice.



agromaster®

+90 332 235 64 23

✉ info@agromaster.com

🌐 www.agromaster.com

🏠 Buyukkayacik OSB Mahallesi Evrenkoy Cad. No:32 42050 Selcuklu/Konya/TURKEY

